

NPS[7]	DN (dimensionless)	OD [in (mm)]	Wall thickness [in (mm)]										
			Sch. 5s	Sch. 10s/20	Sch. 30	Sch. 40s/40	Sch. 80s/80	Sch. 120	Sch. 160	XXS			
						/STD	/XS						
½	3	0.405 (10.29)	0.035 (0.889)	0.049 (1.245)	0.057 (1.448)	0.068 (1.727)	0.095 (2.413)	—	—	—			
¾	6	0.540 (13.72)	0.049 (1.245)	0.065 (1.651)	0.073 (1.854)	0.088 (2.235)	0.119 (3.023)	—	—	—			
1	10	0.675 (17.15)	0.049 (1.245)	0.065 (1.651)	0.073 (1.854)	0.091 (2.311)	0.126 (3.200)	—	—	—			
1½	15	0.840 (21.34)	0.065 (1.651)	0.083 (2.108)	0.095 (2.413)	0.109 (2.769)	0.147 (3.734)	—	—	0.188 (4.775)	0.294 (7.468)		
2	20	1.050 (26.67)	0.065 (1.651)	0.083 (2.108)	0.095 (2.413)	0.113 (2.870)	0.154 (3.912)	—	—	0.219 (5.563)	0.308 (7.823)		
2½	25	1.315 (33.40)	0.065 (1.651)	0.109 (2.769)	0.114 (2.896)	0.133 (3.378)	0.179 (4.547)	—	—	0.250 (6.350)	0.358 (9.093)		
3	32	1.660 (42.16)	0.065 (1.651)	0.109 (2.769)	0.117 (2.972)	0.140 (3.556)	0.191 (4.851)	—	—	0.250 (6.350)	0.382 (9.703)		
3½	40	1.900 (48.26)	0.065 (1.651)	0.109 (2.769)	0.125 (3.175)	0.145 (3.683)	0.200 (5.080)	—	—	0.281 (7.137)	0.400 (10.160)		
4	50	2.375 (60.33)	0.065 (1.651)	0.109 (2.769)	0.125 (3.175)	0.154 (3.912)	0.218 (5.537)	0.250 (6.350)	0.344 (8.738)	0.436 (11.074)			
4½	65	2.875 (73.03)	0.083 (2.108)	0.120 (3.048)	0.188 (4.775)	0.203 (5.156)	0.276 (7.010)	0.300 (7.620)	0.375 (9.525)	0.438 (11.125)	0.552 (14.021)		
5	80	3.500 (88.90)	0.083 (2.108)	0.120 (3.048)	0.188 (4.775)	0.216 (5.486)	0.300 (7.620)	0.350 (8.890)	0.438 (11.125)	0.600 (15.240)			
5½	90	4.000 (101.60)	0.083 (2.108)	0.120 (3.048)	0.188 (4.775)	0.226 (5.740)	0.318 (8.077)	—	—	0.636 (16.154)			

PS[7]	DN[2]	OD [in (mm)]	Wall thickness [in (mm)]											
			Sch. 5	Sch. 10s/10	Sch. 20	Sch. 30	Sch. 40s/40	Sch. 60	Sch. 80s/80	Sch. 100	Sch. 120	Sch. 140	Sch. 160	XXS[7]
4	100	4.500 (114.30)	0.083 (2.108)	0.120 (3.048)	—	0.188 (4.775)	0.237 (6.020)	—	0.337 (8.560)	—	0.437 (11.100)	—	0.531 (13.487)	0.674 (17.120)
4½	115	5.000 (127.00)	—	—	—	—	0.247 (6.274)	—	0.355 (9.017)	—	—	—	—	0.710 (18.034)
5	125	5.563 (141.30)	0.109 (2.769)	0.134 (3.404)	—	—	0.258 (6.553)	—	0.375 (9.525)	—	0.500 (12.700)	—	0.625 (15.875)	0.750 (19.050)
6	150	6.625 (168.28)	0.109 (2.769)	0.134 (3.404)	—	—	0.280 (7.112)	—	0.432 (10.973)	—	0.562 (14.275)	—	0.719 (18.263)	0.864 (21.946)
7	—	7.625 (193.68)	—	—	—	—	0.301 (7.645)	—	0.500 (12.700)	—	—	—	—	0.875 (22.225)
8	200	8.625 (219.08)	0.109 (2.769)	0.148 (3.759)	0.250 (6.350)	0.277 (7.036)	0.322 (8.179)	0.406 (10.312)	0.500 (12.700)	0.593 (15.062)	0.719 (18.263)	0.812 (20.625)	0.906 (23.012)	0.875 (22.225)
9	—	9.625 (244.48)	—	—	—	—	0.342 (8.687)	—	0.500 (12.700)	—	—	—	—	—

PS[7]	DN[2]	OD [in (mm)]	Wall thickness [in (mm)]				
			Sch. 5s	Sch. 10	Sch. 20	Sch. 30	Sch. Std./40S
10	250	10.75 (273.05)	0.134 (3.404)	0.165 (4.191)	0.250 (6.350)	0.307 (7.798)	0.365 (9.271)
12	300	12.75 (323.85)	0.156 (3.962)	0.180 (4.572)	0.250 (6.350)	0.330 (8.382)	0.375 (9.525)
14	350	14.00 (355.60)	0.156 (3.962)	0.250 (6.350)	0.312 (7.925)	0.375 (9.525)	0.375 (9.525)
16	400	16.00 (406.40)	0.165 (4.191)	0.250 (6.350)	0.312 (7.925)	0.375 (9.525)	0.375 (9.525)
18	450	18.00 (457.20)	0.165 (4.191)	0.250 (6.350)	0.312 (7.925)	0.437 (11.100)	0.375 (9.525)
20	500	20.00 (508.00)	0.188 (4.775)	0.250 (6.350)	0.375 (9.525)	0.500 (12.700)	0.375 (9.525)
22	550	22.00 (558.80)	0.188 (4.775)	0.250 (6.350)	0.375 (9.525)	0.500 (12.700)	0.375 (9.525)
24	600	24.00 (609.60)	0.218 (5.537)	0.250 (6.350)	0.375 (9.525)	0.562 (14.275)	0.375 (9.525)